

PROFESSOR SP1R [Prefix: S3\*\*\*\*]

DIAMETER	MSRP	WIDTH	Rim Length / INSET															
			28mm		35mm		41mm		47mm		53mm		66mm		79mm		91mm	
			SL	NR	SL	NR	SL	NR	SL	NR	SL	NR	SL	NR	SL	NR	SL	NR
16 inch	\$610.00	5.5J	45	32														
	\$620.00	6.0J	52	39	45	32	39	26										
	\$630.00	6.5J	58	45	52	39	45	32	39	26	32	19						
	\$640.00	7.0J	52						45	32	39	26	26	13				
	\$650.00	7.5J					58	45			45	32	32	19	19	7		
	\$660.00	8.0J									52	39	26	26	13	13	0	
	\$670.00	8.5J											45	32	32	19	19	7
	\$680.00	9.0J													39	26	26	13
	\$690.00	9.5J															32	19

■ STANDARD P.C.D: 4/100, 4/114.3 ● SL : SUPER LOW DISK , NR : NORMAL DISK

■ SPECIAL P.C.D MSRP +\$25 UP : 4/98~101.65 , 108~114.3

DIAMETER	MSRP	WIDTH	Rim Length / INSET																															
			41mm				53mm				66mm				79mm				91mm				104mm				117mm				130mm			
			SL	NR	MD	HP	SL	NR	MD	HP	SL	NR	MD	HP	SL	NR	MD	HP	SL	NR	MD	HP	SL	NR	MD	HP	SL	NR	MD	HP				
17 inch	\$690.00	6.0J	37	24	16	6																												
	\$700.00	6.5J	43	30	22	12	30	18	10	0																								
	\$710.00	7.0J	49	37	29	19	37	24	16	6	24	11	3	-7																				
	\$720.00	7.5J	55	43	35	25	43	30	22	12	30	18	10	0	18	5	-3	-13																
	\$730.00	8.0J	62	49	41	31	49	37	29	19	37	24	16	6	24	11	3	-7	11	-1	-9	-19												
	\$740.00	8.5J		55	47	37	55	43	35	25	43	30	22	12	30	18	10	0	18	5	-3	-13	5	-8	-16	-26								
	\$750.00	9.0J					62	49	41	31	49	37	29	19	37	24	16	6	24	11	3	-7	11	-1	-9	-19	-1	-14	-22	-32				
	\$760.00	9.5J									55	43	35	25	43	30	22	12	30	18	10	0	18	5	-3	-13	5	-8	-16	-26	-8	-21	-29	-39
	\$770.00	10.0J													49	37	29	19	37	24	16	6	24	11	3	-7	11	-1	-9	-19	-1	-14	-22	-32
	\$780.00	10.5J																	43	30	22	12	30	18	10	0	18	5	-3	-13	5	-8	-16	-26
	\$790.00	11.0J																					37	24	16	6	24	11	3	-7	11	-1	-9	-19
	\$800.00	11.5J																									30	18	10	0	18	5	-3	-13
\$810.00	12.0J																												24	11	3	-7		

■ STANDARD P.C.D: 4/100(SL,NR), 4/114.3(SL,NR), 5/100, 5/114.3 ● SL : SUPER LOW DISK , NR : NORMAL DISK , MD: MEDIUM DISK , HP : HYPER DISK

■ SPECIAL P.C.D MSRP +\$25 UP : ◆ SL , NR : 4/98~101.65 , 108~115 , 5/98~101.65 , 108~115 , 120~120.65 , 127 , 130 ◆ MD , HP : 5/98~101.65 , 108~120.65 , 127 , 130

■ STANDARD COLOR: SILVER, BLACK

■ OPTION COLOR: MSRP +\$25 UP

WHITE, FLAT BLACK, TITAN SILVER, GUNMETAL, FLAT GUNMETAL  
TOURING GOLD, FLARE BRONZE, FLAT FLARE BRONZE

■ SPECIAL COLOR: S.B.C(SUPER BLACK COAT) MSRP +\$120 UP

SPECTRUM SILVER MSRP +\$140 UP

■ ATTACHMENT OPTION: AIR VALVE(LVO-1: PARTS001S), VALVE EXTENSION(PARTS016 1pce/2wheels)

BLACK ANODIZED RIM OUTER RIM MSRP +\$90 UP

BLACK ANODIZED RIM INNER RIM MSRP +\$90 UP

CLASSICAL PIERCE BOLT MSRP +\$60 UP

■ OPTIONAL PART : ALUMINUM CENTER CAP: A-TYPE (SMALL): \$40.00 EACH, B-TYPE(LARGE): \$40.00 EACH

HUB CENTRIC RING (ALUMINUM): \$24.00 PER PAIR

※Please ask us the ETA of SPECIAL P.C.D, OPTION COLOR, SPECIAL COLOR and BLACK ANODIZED RIM.

※Regarding Rim Length 29mm(15inch) and 28mm(16inch) sizes, the disk will stick out from rim.

※Please purchase hubring for Import cars.

※5/112.5/120 cannot be installed on Lexus(LS600h), Audi (RS6 avant), Mercedes Benz (ML63 4MATIC, R350 4MATIC 2012~, GL class, R550 4MATIC, ML350 Blue TEC 4MATIC).

Rolls Royce, Bentley, Maybach, BMW (X5, X5[F15], ActiveHybrid X6) and Land Rover.

※5/130 cannot be installed on Audi(Q7) and Mercedes Benz(G55, G550).

※5/100 cannot be installed on Subaru Legacy Outback (BRF)&Exiga.

※4/100 cannot be installed on Renault Grand Scenic.

HUB CLEARANCE (mm)

SIZE	P.C.D	CAP TYPE	HOLE	DISK	CENTER BORE × HEIGHT				
					DIAMETER	SL	LO	HI	
16inch	98~101.65	A	4/5	SL	φ72.2	26.5	33.0	43.0	
			4	NR	φ72.2	34.5	41.0	51.0	
			5	NR	φ72.2	29.5	36.0	46.0	
	108~114.3	B	4/5	SL	φ79.5	24.5	33.0	43.0	
			4/5	NR	φ79.5	27.5	36.0	46.0	
			4/5	SL	φ72.2	26.5	33.0	43.0	
17inch	98~101.65	A	4/5	NR	φ72.2	29.5	36.0	46.0	
			5	MD	φ72.2	26.5	33.0	43.0	
			5	HP	φ72.2	29.5	36.0	46.0	
		108~127	B	4/5	SL	φ79.5	24.5	33.0	43.0
				4/5	NR	φ79.5	27.5	36.0	46.0
				5	MD	φ79.5	24.5	33.0	43.0
	130	B	5	HP	φ79.5	27.5	36.0	46.0	
			5	SL	φ71.6	24.5	33.0	43.0	
			5	NR	φ71.6	27.5	36.0	46.0	
		130	B	5	MD	φ71.6	24.5	33.0	43.0
				5	HP	φ71.6	27.5	36.0	46.0

※with SSR Aluminum Racing cap