

# Professor SP1R

PROFESSOR SP1R [CODE:S3]

\* Please note that the size of the red text in the specification table protrudes from the rim flange.

REVERSE RIM

SIZE	DISK COLOR / PRICE	STANDARD P.C.D. : 4/100															
		DISK / OUTER RIM LENGTH (mm) / OFFSET															
		SUPER LOW DISK [SL]								NORMAL DISK [NR]							
16 inch	MSRP	28	35	41	47	53	66	79	91	28	35	41	47	53	66	79	91
5.5J	\$720.00	45								32							
6.0J	\$730.00	52	45	39						39	32	26					
6.5J	\$740.00	58	52	45	39	32				45	39	32	26	19			
7.0J	\$750.00			52	45	39	26			52		39	32	26	13		
7.5J	\$760.00			58		45	32	19		45		45		32	19	7	
8.0J	\$770.00					52	39	26	13					39	26	13	0
8.5J	\$780.00						45	32	19						32	19	7
9.0J	\$790.00							39	26							26	13
9.5J	\$800.00								32								19
SPECIAL P.C.D.	+\$25.00	4/98 , 101.65 , 108~114.3															

SIZE	DISK COLOR / PRICE	STANDARD P.C.D. : 4/100 , 5/100 , 5/114.3														STANDARD P.C.D. : 5/100 , 5/114.3																		
		DISK / OUTER RIM LENGTH (mm) / OFFSET																																
		SUPER LOW DISK [SL]							NORMAL DISK [NR]							MEDIUM DISK [MD]						HYPER DISK [HP]												
17 inch	MSRP	41	53	66	79	91	104	117	130	41	53	66	79	91	104	117	130	41	53	66	79	91	104	117	130	41	53	66	79	91	104	117	130	
6.0J	\$800.00	37								24								16								6								
6.5J	\$810.00	43	30							30	18							22	10							12	0							
7.0J	\$820.00	49	37	24						37	24	11						29	16	3						19	6	-7						
7.5J	\$830.00	55	43	30	18					43	30	18	5					35	22	10	-3					25	12	0	-13					
8.0J	\$840.00	62	49	37	24	11				49	37	24	11	-1				41	29	16	3	-9				31	19	6	-7	-19				
8.5J	\$850.00		55	43	30	18	5			55	43	30	18	5	-8			47	35	22	10	-3	-16			37	25	12	0	-13	-26			
9.0J	\$860.00		62	49	37	24	11	-1			49	37	24	11	-1	-14			41	29	16	3	-9	-22			31	19	6	-7	-19	-32		
9.5J	\$870.00			55	43	30	18	5	-8			43	30	18	5	-8	-21			35	22	10	-3	-16	-29			25	12	0	-13	-26	-39	
10.0J	\$880.00				49	37	24	11	-1				37	24	11	-1	-14				29	16	3	-9	-22				19	6	-7	-19	-32	
10.5J	\$890.00					43	30	18	5					30	18	5	-8					22	10	-3	-16					12	0	-13	-26	
11.0J	\$900.00						37	24	11						24	11	-1						16	3	-9						6	-7	-19	
11.5J	\$910.00							30	18							18	5								10	-3							0	-13
12.0J	\$920.00								24								11									3								-7
SPECIAL P.C.D.	+\$25.00	4/98 , 101.65 , 108~114.3 · 5/98 , 101.65 , 108~120.65 , 127 , 130														5/98 , 101.65 , 108~120.65 , 127 , 130																		

REVERSE RIM

- STANDARD COLOR : SILVER, BLACK
- OPTIONAL COLOR : +\$25.00 MSRP PER WHEEL  
WHITE, FLAT BLACK, FLAT SILVER, TITAN SILVER, HIGH BRIGHT SILVER, DIAMOND SILVER, HIGH METAL BRONZE, CRYSTAL SILVER, GUNMETAL, FLAT GUNMETAL, PRIZM DARK GUNMETAL, FLAT GOLD, TOURING GOLD, FLARE BRONZE, FLAT FLARE BRONZE, PINK, LIGHT YELLOW, MINT GREEN, MARINE BLUE, BLUE GUNMETAL
- SPECIAL COLOR : SPECTRUM SILVER +\$140.00 MSRP PER WHEEL  
SUPER BLACK COAT +\$120.00 MSRP PER WHEEL
- INCLUDED PARTS : AIR VALVE (LVO-1D:PARTS500S)  
LOGO STICKER (SSR SILVER:PARTS330)
- OTHER OPTION : BLACK ANODIZED OUTER RIM +\$90.00 MSRP PER WHEEL, BLACK ANODIZED INNER RIM +\$90.00 PER WHEEL  
GOLD PIERCE BOLTS +\$70.00 MSRP PER WHEEL \*17inch only, CLASSICAL PIERCE BOLTS +\$60.00 MSRP PER WHEEL \*17inch only
- OPTIONAL PARTS : ■ SSR ALUMINUM CENTER CAP / SSR ALUMINUM CENTER CAP (BLACK ANODIZED)  
A-TYPE (P.C.D.100) HIGH(PARTS229S1) / LOW(PARTS228S1) / SL(PARTS241S1) \$40.00  
A-TYPE[BLACK] (P.C.D.100) HIGH(PARTS229BL) / LOW(PARTS228BL) / SL(PARTS241BL) \$55.00  
B-TYPE (P.C.D.112,114.3,120) HIGH(PARTS227S1) / LOW(PARTS226S1) / SL(PARTS240S1) \$40.00  
B-TYPE[BLACK] (P.C.D.112,114.3,120) HIGH(PARTS227BL) / LOW(PARTS226BL) / SL(PARTS240BL) \$55.00

## HUB CLEARANCE(mm)

SIZE	P.C.D.	CAP TYPE	HOLE	DISK	CENTER BORE × HEIGHT				
					DIAMETER	SL	LO	HI	
16inch	98~101.65	A	4	SL	φ72.2	26.5	33.0	43.0	
			4	NR	φ72.2	34.5	41.0	51.0	
	108~114.3	B	4	SL	φ79.5	24.5	33.0	43.0	
			4	NR	φ79.5	27.5	36.0	46.0	
		4/5	SL	φ72.2	26.5	33.0	43.0		
			NR	φ72.2	29.5	36.0	46.0		
17inch	98~101.65	A	5	MD	φ72.2	26.5	33.0	43.0	
			5	HP	φ72.2	29.5	36.0	46.0	
		4/5	SL	φ79.5	24.5	33.0	43.0		
			NR	φ79.5	27.5	36.0	46.0		
		108~127	B	4/5	NR	φ79.5	27.5	36.0	46.0
				5	MD	φ79.5	24.5	33.0	43.0
	5		HP	φ79.5	27.5	36.0	46.0		
			SL	φ71.6	24.5	33.0	43.0		
	130	B	5	NR	φ71.6	27.5	36.0	46.0	
			5	MD	φ71.6	24.5	33.0	43.0	
5		HP	φ71.6	27.5	36.0	46.0			
		SL	φ71.6	24.5	33.0	46.0			